

ECO PLUS SERIES



ECOPLUS 100



PERFORMANCE FEATURES

Shadow Free
Illumination

1

2

Laminar Air Flow
Compatibility and
compact Design

Auto Focus

3

4

Efficient Focus
on LEDs

Multi Lens
System

5

6

Beam Formation

Remote Control &
Sterilizable Handle

7

8

Suturing light for
Convenient Post
Operative Procedure

TECHNICAL SPECIFICATION

PARAMETERS	ECOPLUS 100
Illumination Intensity	100000 Lux
LED Service Life	50,000 hours
Color Temperature	5500 K
Color Rendering Index	95 Ra
Temperature Increase at Surgeon head Area	<2 deg C
Index Light Spot	210-280mm
Brightness Adjustment	0 to 100%
Power	230 VAC/50/60 Hz
Auto Focus	Available
Laminar Air Flow	Available
Compact Design	Yes
Shadow Free Illumination	Yes
Multi Lens System	Yes
Beam Formation - Hot Spot	Yes
Suturing light for Post Operative Procedure (Low Intensity)	Yes
Remote Control (On/off switch, light)	Yes
Sterilizable Handle	Yes

AVAILABLE CONFIGURATION

Mobile

- Eco plus 140
- Eco plus 100

Celing

- Eco plus 140
- Eco plus 100
- Eco Plus 100 + 100
- Eco Plus 100 + 140
- Eco Plus 140 + 140

ECOPLUS 100

